

KENWOOD

Listen to the Future



TK-6110

Compact VHF Low Band Mobile Radio

GENERAL FEATURES

- 70 W (29.7-37.0, 35.0-50.0 MHz)
- 32 Channels
- Single Priority Scan
- 8 Character Alphanumeric LCD
- 3 Digit Sub-Display and Icons
- Transmit / Busy / Call Allert / Warn LED
- Up/Down Channel Selector
- Volume Knob
- Power On/Off Button
- 7 Programmable Radio Keys
- Front Panel Speaker
- Noise Blanker Function
- Encryption / ANI Board Control
- Emergency Call Features
- QT/DQT Encode & Decode
- Operator Selectable Tone
- Two Tone Decode
- DTMF Encode & Decode
- Time Out Timer
- Busy Channel Lockout
- 15 Pin Accessory Connector
- MIL-Spec / Noise-Cancel Microphone
- M-Type Antenna Connector
- Ignition Sense
- Timed Power Off
- Horn Alert
- Cloning
- PC Programming & Tuning
- MIL-STD-810 C/ D/ E



Options

- **KMC-9C**
Control Station
Desktop Microphone



- **KMC-27A**
Microphone
(supplied microphone)



- **KMC-27B**
Microphone
(MIL-SPEC noise-canceling)



- **KMC-28A**
Keypad Microphone
(MIL-SPEC noise-canceling)



- **KCT-18**
Ignition Sense Cable



- **KLF-2**
Line Noise Filter



- **KES-5**
External Speaker



All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

Model	TK-6110
GENERAL	
Frequency Range	
Type 1	29.7-37.0 MHz
Type 2	35.0-50.0 MHz
Number of Channels	32
Channel Spacing	
	20 kHz / 25 kHz
Channel Step	5 kHz
Operating Voltage	13.6 V DC ±15%
Current Drain	
Standby	< 0.6 A
Receive	< 2.4 A
Transmit	< 15 A
Duty Cycle	Transmit: 20%
Operating Temperature Range	-22°F ~ +140°F (-30°C ~ +60°C)
Frequency Stability (-22° F - +140° F)	±0.0005%
Antenna Impedance	50 Ω
Dimensions (W x H x D)	6-1/4 x 2 x 6-1/4 in.
Projections not included	(160 x 50 x 160 mm)
Weight (net)	3.5 lbs. (1.6kg)
FCC ID	
Type 1	ALH29351110
Type 2	ALH29351120
IC Certification	
Type 1	
Type 2	282195666A
RECEIVER (Measurements made per EIA/TIA-603)	
Sensitivity (12dB SINAD)	0.25µV
Selectivity	75 dB
Intermodulation Distortion	70 dB
Spurious Response	70 dB
Audio Output	10W at less than 5% distortion
Band Spread	
Type 1	7.3 MHz
Type 2	15.0 MHz
TRANSMITTER (Measurements made per EIA/TIA-603)	
RF Output Power	70 W
Type of Emission	16K0F3E
Spurious Response	62 dB
FM Hum & Noise	50 dB
Microphone Impedance	600 Ω
Audio Distortion	Less than 3%
Band Spread	
Type 1	7.3 MHz
Type 2	15.0 MHz

Kenwood follows a policy of continuous advancement in development. For this reason specifications may be changed without notice.

Unavailable Frequencies:
TK-6110K (29.7 - 37.0 MHz model): 33.60 MHz
TK-6110K2 (35.0 - 50.0 MHz model): 42.00 MHz

Applicable MIL-STD

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV



ISO9001 Registered
Communications Equipment Division
Kenwood Corporation
ISO9001 certification

ADS#43907 Printed in USA

KENWOOD



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>