


Home Theater Package with 6 Speakers

**DENON****DHT-484XP****DHT-484XP Home Theater Package with 6 Speakers**

#### ■ DENON's Basic Design for High-Quality Sound Reproduction

##### • Power Transformer for High Power Driven

The chassis that supports the large transformer has been designed to absorb vibration, and the transformer is housed inside a highly rigid frame to secure it more solidly to the chassis. In addition, a cushioning material has been placed around the core of the transformer to minimize interference on the signal and enable more faithful reproduction of the original sound. The AVR-484 inherits these low-noise design from higher-end models not to mention the use of short ring.



##### • Twin Drive Rectifier

DENON's Twin Drive Rectifier design uses two rectifying diodes in parallel to bring out the maximum potential of the large transformer. Since the rectifiers recharge the large block capacitors at low impedance, they are able to supply ample current to reproduce deep basses as well as sudden bursts of sound from percussion or other musical instruments.

##### • Large Aluminum Extruded Heatsink

DENON uses large heatsink made of extruded aluminum. It has been placed in a design that ensures mostly uniform temperatures throughout the heatsink. This in turn ensures that all channels respond with equal performance to the demands of the audio signals.



#### ■ Fully Discrete, Equal Power Five Amplifier Channels, 110 Watts Each

Front	110 W + 110 W	(6 ohms, 1 kHz, 0.7 % THD)
Center	110 W	(6 ohms, 1 kHz, 0.7 % THD)
Surround	110 W + 110 W	(6 ohms, 1 kHz, 0.7 % THD)

For optimum Dolby Digital and DTS reproduction, the AVR-484 features high quality, wideband audio amplification, providing 110 watts power output for each of the five main channels. A large capacity power supply includes a high current power transformer along with discrete power output devices on all five amplifier channels for the highest dynamic range and superb reproduction clarity.

#### ■ 24 bit High Resolution DSP

#### ■ 24 bit, 96 kHz High Resolution D/A Conversion

#### ■ Wide-Range Play Capability for DVD-Audio and Super Audio CD

The power amp circuits of the AVR-484 have been meticulously designed to reproduce the exceptionally high sound quality with wide frequency response from 10 Hz to 100 kHz.

#### ■ Cinema Equalizer

The sound from movie sources recorded in Dolby Digital, DTS or other formats emphasizes high-frequency range due to a theater's front speakers being placed



SC-U54HTB (SC-U54S/SC-U54C/DSW-80)

\*The speaker system shown is not available in some markets.

behind the movie screen. If this sound is reproduced in the home theater without correction, the high-frequency range is too strong. The AVR-484 features a Cinema Equalizer to correct these high-frequency components so that the sound is clearer and easier to listen to. (For Dolby Digital, Dolby Pro Logic II, and DTS surround modes)

#### ■ Personal Memory Plus, for Easy Operation

The AVR-484 includes the Personal Memory Plus function that automatically remembers the surround mode you last used for each program source, so that you do not need to select the mode again for that program.

#### ■ Acclaimed Customization Feature

As with all of DENON's high-grade A/V receiver, the AVR-484 lets you adjust delay times and other parameters so that you can customize the performance of the AVR-484 to suit your own home theater and enhance operating ease. The adjustments are easy to make via a dialog format on the fluorescent display on the front panel. These customized features are then stored, for each source input and surround mode, in Personal Memory Plus so constant readjustments are not required.

#### ■ Multi-Function Preset Memory Remote Controller with Glo-keys

The supplied system remote controller features a large selection of remote control codes to operate other components in your home theater system, including codes for selected DENON models, along with remote control codes from other manufacturers. The most frequently used buttons are laid out separately for TV, VCR and DVD, for maximum ease-of-use.

\* Remote control codes may not be available for some products of other manufacturers.

#### ■ Dolby Pro Logic II Decoder

Enjoy 2-channel stereo recordings in stunning 5.1-channel surround playback. The Dolby Pro Logic II decoder reproduces dynamic 5.1-channel surround sound not only from normal 5.1-channel DVD but from 2-channel sources such as videos and CDs, too. Dolby Pro Logic II uses matrix decoding technology that has been dramatically improved over Pro Logic.

### ■ Dolby Digital and dts Decoders

Equipped with both Dolby Digital and dts 5.1 channel decoding, the AVR-484 provides thrilling surround sound with the thousands of Dolby Digital and dts encoded DVDs, as well as the growing library of dts 5.1 channel music recordings available on CD.

### ■ 5 Channel Stereo Mode

DENON's popular 5 Channel Stereo mode transforms your favorite 2-channel sources such as CD, tape, stereo radio and stereo video sources into exciting surround sound, free of delay effects and unnatural artifacts, from all five speakers. This 5 Channel Stereo mode was originally developed by DENON to enhance music lovers' enjoyment with home theater ambience.

### ■ Virtual Surround Mode

Surround yourself with sensational 3D soundfield envelopment using just one pair of speakers. The AVR-484's Virtual Surround mode provides a dramatic psychoacoustic surround sound effect, using two speakers with Dolby Digital 5.1 encoded sources.

### ■ DENON DSP Surround Modes Add Listening Excitement

Put yourself in the middle of your favorite concert hall and music environments with DENON's DSP acoustic environment simulation modes. These DSP modes add spacious surround sound enhancements to your favorite music and video sources, and include these distinctively different sounding modes:

1. 5 Channel Stereo
2. Virtual Surround
3. Rock Arena
4. Jazz Club
5. Video Game
6. Matrix
7. Mono Movie

### ■ Front Panel Inputs

### ■ Front A/B Speaker Terminals

### ■ High-grade 5 Channel Speaker Terminals (except speakers B)

### ■ Frequency Synthesis Tuning

- 40-Station AM/FM Random Preset Memory Tuning
- Auto Preset Memory

### Specifications

#### ■ Input/Output Terminals For Every A/V System

##### • Audio Inputs

- 7 Analog Inputs..... CD, TUNER, DVD/VDP, TV/DBS, VCR, CDR/TAPE, V.AUX(FRONT)
- 6 Analog EXT. Input ..... FRONT L/R, CENTER, SURROUND L/R, SUBWOOFER
- 1 Digital (Optical) Input ..... OPTICAL X 1
- 1 Digital (Coaxial) Input ..... COAXIAL X 1

##### • Audio Outputs

- 1 Analog PRE OUT Terminals..... SUBWOOFER
- 2 Analog REC OUT Terminals..... VCR, CDR/TAPE

##### • Video Inputs

- 4 Composite Inputs..... DVD/VDP, TV/DBS, VCR, V.AUX(FRONT)
- 3 S-Video Inputs ..... DVD/VDP, TV/DBS, VCR

##### • Video Outputs

- 2 Composite Outputs..... VCR, MONITOR
- 2 S-Video Outputs ..... VCR, MONITOR

### ■ Power Amplifier Section

Rated output	*THD figures are power amp stage values.	
Front.....	75 W + 75 W	(8 ohms, 20 Hz - 20 kHz, 0.08 % THD)
	110 W + 110 W	(6 ohms, 1 kHz, 0.7 % THD)
Center.....	75 W	(8 ohms, 20 Hz - 20 kHz, 0.08 % THD)
	110 W	(6 ohms, 1 kHz, 0.7 % THD)
Surround.....	75 W + 75 W	(8 ohms, 20 Hz - 20 kHz, 0.08 % THD)
	110 W + 110 W	(6 ohms, 1 kHz, 0.7 % THD)

### ■ Preamp Section

Input sensitivity/Impedance	CD, DVD/VDP, TV/DBS, VCR, CDR/TAPE, V.AUX(FRONT).....	200 mV/47 kohms
Output level/Load impedance	SUBWOOFER.....	1.2 V/10 kohms
	CDR/TAPE, VCR.....	200 mV/47 kohms
Frequency response.....	10 Hz - 100 kHz (+1, -3 dB) (Tone Defeat On)	
Signal-to-noise ratio.....	98 dB (IHF-A weighted) (Tone Defeat On)	
Tone control.....	Treble: ±10 dB at 10 kHz	
	Bass: ±10 dB at 100 Hz	

### ■ FM Section

Tuning frequency range.....	87.5 - 107.9 MHz
Usable sensitivity.....	1.0 μV (11.2 dBf)

### ■ AM Section

Tuning frequency range.....	520 - 1710 kHz
Usable sensitivity.....	18 μV

### ■ General

Power supply.....	AC 120 V, 60 Hz
Power consumption.....	3.8 A
Dimensions.....	434 (W) x 147 (H) x 417 (D) mm
	17.1" (W) x 5.8" (H) x 1.4" (D)
Weight.....	10.3 kg, 22.7 lbs

### ■ Speaker section

#### SC-U54S (Satellite speaker system)

Type.....	2-way Acoustic Suspension
Magnetic shielding.....	Yes
Impedance.....	6 ohms
Dimensions.....	131 (W) x 175 (H) x 130 (D) mm (+19 mm grill)
	5.2" (W) x 6.9" (H) x 5.1" (D)
Weight.....	1.9 kg, 4.1 lbs

#### SC-U54C (Center speaker system)

Type.....	2-way Acoustic Suspension
Magnetic shielding.....	Yes
Impedance.....	6 ohms
Dimensions.....	276 (W) x 131 (H) x 130 (D) mm (+19 mm grill)
	10.9" (W) x 5.2" (H) x 5.1" (D)
Weight.....	3.0 kg, 6.6 lbs

#### DSW-80 (Subwoofer system with built-in Amplifier)

Impedance.....	4 ohms
Power supply.....	AC 120 V, 60 Hz, 90 W
Dimensions.....	478 (W) x 288 (H) x 393 (D) mm (with feet)
	18.8" (W) x 11.3" (H) x 15.5" (D)
Weight.....	12.5 kg, 27.5 lbs



\*Design and specifications are subject to change without notice.

\*\*Dolby®, "Dolby Digital", "Pro Logic II", and the double-D device are registered trademarks of Dolby Laboratories Licensing Corporation.

\*DTS is registered trademarks of DTS Technology.

DENON ELECTRONICS (USA) INC.  
19 CHAPIN ROAD, P.O. BOX 867, PINE BROOK, NJ 07058-9777 USA  
TEL: 973-396-0810 www.usa.denon.com

DENON CANADA INC.  
17 DENISON STREET, MARKHAM ONTARIO, CANADA L3R 1B5  
TEL: 905-475-4085 www.denon.ca

DENON, LTD.  
3-16-11, YUSHIMA, BUNKYO-KU, TOKYO 113-0034, JAPAN

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>