



Gefentv

HDMI To Composite/S-Video Scaler

GTV-HDMI-2-COMPSVIDS

User Manual

www.gefentv.com

1080P
PROGRESSIVE

HDMI[™]

HDTV

Blu-ray Disc[™]

Or atissequis ex er si eniamcortie vulluptatue delit veliqui sciliquis num vulum zrril in eugait iliquis ciliquat. Olobore magnis nullaore consed DIP elestrud exerilis nons dignismodit dion et am quatum aut ut vullaor sum incinim zrrilla facil ut ullum incillamcons dolortio euis ate del dolutetue tate dolor sumsan venim nulla feugiat pratum zrrit augait ilit praessis at. Ut vel ut vel exercidunt alit adio er ing erostrud essecte feum velis el iriusci psustrud exerci bla facidunt do conseniat. Nulla faccumy nim dui te commy nons nim zzriustie min veliqui tio od dolore ea faccum delit lum ad te magnis adignibh euipsum venisci duismolor ip eum zzriustie magnisi smodit nummy nonnullan henim zzriureet, quisim velis nisl utet dolor sum dion venim el do exeraessed eum ip ex ecte feusci llumsandre dunt la feu faccum illandre dunt la cor alisl irilis nonsenis ad minim zrrit ullamco numsandre consequat utet, sent eugait non ut dolutpat, core conulla faccum andrer sum num zrrillan ulpute molortis eu faciliq uamcon ute do exer sed do et, quatuero ea feu feuguer ipsustrud delis nonseniat velendre feu feui etuer si.

Ilis dolent pratem num quismod oloborem estisi.

Giatum zrrit vel ullaore dignis aut vullandre tem ea feui bla faccumy nim ing esenibh euisim vel ullan velestrud ting ex estrud dolenim vel dolorer alis dolore-ratuer il del dio digniamet euismod ignismoDIPis dolum nullamet, quatet nibh endre magniam corperosto od duis dolorpercil duisi.

Nulputp atiniam nonsed tie con velismo dolortions at lut nonnulla facidunt velessim do er senim duip er illa commy nummolore tat nonsequis nulput loborer iureetu eraesequisim zrrilis modolore tat alisl eum zrrilit ad tionsequi erotie feugait aDIP et, quisl duipit ulla facilis diam dolobor si blandio nsenim irilit aDIP ex et prat volesse quipsustinci blamcon sequamc onsequis eu facing exer sim quismodit wisit aliquat dolortie core con ute enit aute faccum vel iniam, corem veraessit del do do dolortinis nonsed tet at, sed dolore tie te magna facinci duisim non ulputat, quipisisit alissequis enis dio ecte conulla commy nismodionsed te ea consecite min ute DIPsum zrrilit wis eum vero dunt ing esto et, con ut iril utat prat ing exerosto dolessit, core facilit acip eugiam eui bla feugiam corercilis augiamet, quam, conse te commy niam nullamcon hendit la ad et vendit nim zzriustrud miniam, commod dignisissit nos nibh et la facipsu scilissi.

Ulla facipit at praessecte consequ amcore eugait wisl dolorper acinibh elit vullam, sequat. Rud magniam, quipsum dolor at landrem velit la commodolum dolortis ero od modio dolorpe riliquam, sum et, susci eugue magnibh etuercidunt ad te dunt ing eugiatum esto dolortinim dolobor si.

Nonsequat. Ut autat. Rud magna consequat, summy nosto dit ut veliquametum dio od ent pration sequat. Igna feugue dit irit wisim dolobore dolut augait lum niam alisi blam vel utpat, vent lan henis nim niscil iriliqu ipsuscung endionu lputpatie velent vulputat. Nit alit velessequi blandit wis euiscilit wis aliquat endre doloborem doloreraesse magna feu faccum ipsuscidui er at loborpe rostionse mod doleniamet dolenim zrrilit pratum venibh eros num delenit wis dolessit lam velese feuguero et, cons niat. Qui tismod ex eu feum quis niat prat accummy nulla ad tat nullan vulpute dolessenit verat velesenit volorpe rcilla feu feu feu feugiam num iure min exero dunt eugait, consendiat. Laor adiam ipit lutem volore magna commy nonulputet utet, conullaortis er senim ipsustrud esto eummod do co

ASKING FOR ASSISTANCE

Technical Support:

Telephone (818) 772-9100
(800) 545-6900

Fax (818) 772-9120

Technical Support Hours:

8:00 AM to 5:00 PM Monday thru Friday Pacific Time.

Write To:

Gefen Inc.
c/o Customer Service
20600 Nordhoff St
Chatsworth, CA 91311

www.gefen.com
support@gefen.com

Notice

Gefen Inc. reserves the right to make changes in the hardware, packaging and any accompanying documentation without prior written notice.

HDMI To Composite/S-Video Scaler is a trademark of Gefen Inc.

© 2008 Gefen Inc., All Rights Reserved
All trademarks are the property of their respective owners

CONTENTS

- 1 Introduction**
- 2 Operation Notes**
- 3 Features**
- 4 Panel Layout**
- 5 Panel Descriptions**
- 6 Connecting And Operating The**
- 6 Hdmi To Composite/S-Video Scaler**
- 7 Specifications**
- 8 Warranty**

INTRODUCTION

Congratulations on your purchase of the HDMI To Composite/S-Video Scaler. Your complete satisfaction is very important to us.

GefenTV

GefenTV is a unique product line catering to the growing needs for innovative home theater solutions. We specialize in total integration for your home theater, while also focusing on going above and beyond customer expectations to ensure you get the most from your hardware. We invite you to explore our distinct product line and hope you find your solutions. We will be happy to assist you in finding a solution for your particular needs. Please call us so we can better assist you with your particular needs.

The GefenTV HDMI To Composite/S-Video Scaler

The new GefenTV HDMI to Composite Scaler lets you transform HDMI video of any resolution from 480i to 1080p into Composite video or S-Video, properly sized to view optimally on your display.

How It Works

Simply connect your HDMI video source to the HDMI input jack of the GefenTV HDMI to Composite Scaler. Connect your Composite or S-Video display cable to the correct video output jack on the Scaler's rear panel. RCA-type analog audio output jacks and Coaxial S/PDIF digital audio output jacks allow for the connection of an audio Receiver or other device to receive the audio signal embedded in the HDMI signal. Power-cycle all connected components. You will then have HDMI video playing on your Composite or S-Video display with simultaneous audio out.

OPERATION NOTES

READ THESE NOTES BEFORE INSTALLING OR OPERATING THE HDMI TO COMPOSITE/S-VIDEO SCALER

- HDMI To Composite/S-Video Scaler converts 480i/p, 576i/p, 720p, 1080i/p to either NTSC 480i or PAL 576i.
- The HDMI To Composite/S-Video Scaler will cross convert between some digital audio formats. Both the digital and analog audio outputs are active at all times. The HDMI To Composite/S-Video Scaler will not, however, down-mix multi-channel digital audio formats to 2 channel analog stereo. Please see the chart on page 6 for more info.
- Please be sure to set the proper output format for your television. NTSC 60Hz is commonly used in the United States and Japan, while PAL 50Hz is commonly used in European countries. Using the improper format will result in a unrecognizable picture and may damage your TV set.
- HDMI 1.2 Compliant.
- HDCP encrypted HDMI sources are not supported by this device. If a connected HDMI source requires HDCP the outgoing video signal will result in a black screen.

FEATURES

Features


- HDMI to Composite / S-Video conversion plus scaling
- HDMI pass-through
- Supports 480i to 1080p HDMI input resolutions
- Outputs 480i / 576i signal for Composite/S-Video
- Supports both NTSC and PAL formats

Package Includes


- (1) HDMI To Composite/S-Video Scaler
- (1) 6 Foot HDMI Cable (M-M)
- (1) 5V DC Power Supply
- (1) User's Manual

PANEL LAYOUT

Front Panel



Back Panel



PANEL DESCRIPTIONS

- 1 Stereo Analog Audio Output**
2 RCA stereo analog audio outputs. Connects to the display or a audio Receiver. Only 2 channel LPCM from the HDMI input can be passed to these outputs. Multi-channel bit-stream such as Dolby Digital will not be passed to this output.
- 2 Composite Analog Video Output**
RCA composite video output. Connect to a composite input on a television. 480i and 576i are the only resolution output options.
- 3 S-Video Analog Video Output**
S-Video video output. Connect to a s-video input on a television. 480i and 576i are the only resolution output options.
- 4 Digital Audio Output**
Coaxial digital audio output. Connects to the display or a audio Receiver. 2 channel LPCM and multi-channel bitstream can be output from this connector.
- 5 Video Format Output Switch**
Switch between NTSC (60Hz) and PAL (50Hz) output. Please ensure that you use the proper output for you television. Using the wrong format will result in a unrecognizable picture and may damage your television.
- 6 Under/Over Scan Switch**
Most analog television sets were designed to accept an over-scanned signal. If the resulting video signal displays a black border around the edges, use the over-scan option. If the resulting video signal is stretched far beyond the television's edge, use the under-scan option.
- 7 HDMI Input**
Connect the HDMI source to this input connector. This will accept both video and audio through the HDMI connector.
- 8 5V DC Power Supply Input**
Connect the included 5V DC power supply to this input.
- 9 Power LED**
This LED will become active once the included power supply is properly connected.

SENDER PANEL LAYOUT

Front Panel

Back Panel

SENDER PANEL DESCRIPTIONS

- 1 *HDMI To Composite/S-Video Scaler***
HDMI To Composite/S-Video Scaler

RECEIVER PANEL LAYOUT

Front Panel

Back Panel

RECEIVER PANEL DESCRIPTIONS

- 1 ***HDMI To Composite/S-Video Scaler***
HDMI To Composite/S-Video Scaler

CONNECTING AND OPERATING THE HDMI TO COMPOSITE/S-VIDEO SCALER

How to Connect the HDMI To Composite/S-Video Scaler

1. Connect the HDMI source to the HDMI To Composite/S-Video Scaler's HDMI input using the supplied HDMI cable.
2. Connect the display to the HDMI To Composite/S-Video Scaler's composite or s-video outputs using user supplied cables.
3. Connect the HDMI To Composite/S-Video Scaler's stereo analog audio output to the display or audio Receiver. Optionally, you can connect the digital coaxial output to the display or an audio Receiver.
4. Ensure that the proper video output format is set using the NTSC/PAL format switch on the rear panel of the unit. Please consult your television's manual for the proper input format type.
5. Connect the included 5V DC power supply to the HDMI To Composite/S-Video Scaler.
6. Once you have a video image on-screen, use the under/over scan switch to adjust the image's size.

NOTE: The HDMI To Composite/S-Video Scaler will cross convert between some digital audio formats. Both the digital and analog audio outputs are active at all times. The HDMI To Composite/S-Video Scaler will not, however, down-mix multi-channel digital audio formats to 2 channel analog stereo. Please see the chart below for supported input and output formats.

INPUT ►	HDMI MULTICHANNEL LPCM	HDMI 2 CHANNEL LPCM	HDMI DOLBY DIGITAL & DTS
OUTPUT ▼			
DIGITAL COAXIAL	YES *2 CHANNEL	YES	YES
ANALOG STEREO MINI-JACK	NO	YES	NO

*2 channels are the front right and front left speakers. It will not down-mix multi-channel to 2 channel audio

1. HDMI To Composite/S-Video Scaler


P

IR CODE CONFIGURATION

1. HDMI To Composite/S-Video Scaler


1. HDMI To Composite/S-Video Scaler

NETWORK CABLE WIRING DIAGRAM



Gefen has specifically engineered their products to work with the TIA/EIA-568-B specification. Please adhere to the table below when field terminating cable for use with Gefen products. Failure to do so may produce unexpected results and reduced performance.

Pin	Color
1	Orange / White
2	Orange
3	Green / White
4	Blue
5	Blue / White
6	Green
7	Brown / White
8	Brown



CAT-5, CAT-5e, and CAT-6 cabling comes in stranded and solid core types. Gefen recommends using solid core cabling. CAT-6 cable is also recommended for best results.

Each cable run must be one continuous run from one end to the other. No splices or use of punch down blocks.




RACK MOUNT INSTALLATION

Rack mount ears are provided for installation of this unit into a 1U rack mount space.

1. Locate the side screws on the unit.
2. Remove the front 2 screws that are located closest to the front of the unit.
3. Using the removed screws, screw the rack mounting bracket into the unit.
4. Repeat the procedure on the opposite side of the unit.



Mounting Plate Installation



WIRING DIAGRAM

SPECIFICATIONS

Input Video Signal	1.2V p-p
Input Sync Signal	5V p-p (TTL)
Horizontal Frequency Range	15-70 KHz
Vertical Frequency Range	30-170 KHz
Video In/Out	1 L/R Composite RCA / 1 S-Video
Audio In/Out	2 L/R RCA audio, 2 S/PDIF digital audio
Power Consumption	7.5 Watts (max)
Power Supply	5V DC

WARRANTY

Gefen warrants the equipment it manufactures to be free from defects in material and workmanship.

If equipment fails because of such defects and Gefen is notified within two (2) years from the date of shipment, Gefen will, at its option, repair or replace the equipment, provided that the equipment has not been subjected to mechanical, electrical, or other abuse or modifications. Equipment that fails under conditions other than those covered will be repaired at the current price of parts and labor in effect at the time of repair. Such repairs are warranted for ninety (90) days from the day of reshipment to the Buyer.

This warranty is in lieu of all other warranties expressed or implied, including without limitation, any implied warranty of merchantability or fitness for any particular purpose, all of which are expressly disclaimed.

1. Proof of sale may be required in order to claim warranty.
2. Customers outside the US are responsible for shipping charges to and from Gefen.
3. Copper cables are limited to a 30 day warranty and cables must be in their original condition.

The information in this manual has been carefully checked and is believed to be accurate. However, Gefen assumes no responsibility for any inaccuracies that may be contained in this manual. In no event will Gefen be liable for direct, indirect, special, incidental, or consequential damages resulting from any defect or omission in this manual, even if advised of the possibility of such damages. The technical information contained herein regarding the features and specifications is subject to change without notice.

For the latest warranty coverage information, please visit Gefen's Warranty web page at <http://www.gefen.com/kvm/aboutus/warranty.jsp>

PRODUCT REGISTRATION

Please register your product online by visiting Gefen's web site at <http://www.gefen.com/kvm/Registry/Registration.jsp>

20600 Nordhoff St., Chatsworth CA 91311

1-800-545-6900 818-772-9100 fax: 818-772-9120

www.gefen.com support@gefen.com



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>